ASSIGNED 19 30869

APPLICATION FOR PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF NEVADA

Date of filing in State Engineer's Office. DEC 1 1976
Returned to applicant for correction.
Corrected application filed
Map filed March 23, 1972 under 26628
7 The state of the state
The applicant Agri-Technology Corporation
3429 So. Carson Sp 16 of Carson City Street and No. or P.O. Box No. City or Town
Nevada 89%01 , hereby make application for permission to appropriate the public State and Zip Code No.
waters of the State of Nevada, as hereinafter stated. (If applicant is a corporation, give date and place of incorpora-
tion; if a copartnership or association, give names of members.) Corporation State of
Nevada 1971 · · · · · · · · · · · · · · · · · · ·
1. The source of the proposed appropriation is <u>underground</u> Name of stream, lake or other source.
2. The amount of water applied for issecond-feet One second-foot equals 448.83 gals. per min.
(a) If stored in reservoir give number of acre-feetacre-feet
3. The water to be used for domestic and industrial Irrigation, power, mining, manufacturing, domestic, or other use.
4. If use is for:
(a) Irrigation (state number of acres to be irrigated)
(b) Stockwater (state number and kinds of animals to be watered)
(c) Other use (describe fully under "No. 12, Remarks")
(d) Power:
(1) Horsepower developed
(2) Point of return of water to stream
5. The water is to be diverted from its source at the following point NE SW Section 16 24 RWB. T 15 N, R 25 E. M.D.B.&M. ar at a point from which the SENE corner of said section 24 16 RWB. bears N 55° 49', 50 E. a distance of
Describe as being within a 40-acre subdivision of public survey, and by course and distance to a section corner. If on unsurveyed land,
4,792.30 feet. it should be stated.
6. Place of use NW 4 SW 4 section 15; N 2 SE 4, SW 4 SE 4, NE 4 SW 4 section 16; Describe by legal subdivision, if on unsurveyed land it should be so stated.
N2-section-20;-NW2;-N2-SW2-section-21;-all-in-T-15-N;-R-25-E; RWB.
M-D-B-&-M.
7. Use will begin about Jan 1st and end about Dec 31st of each year. Day and Month Day and Month
Day and Month Day and Month 8. Description of proposed works. (Under the provisions of NRS 535.010 you may be required to submit plans and
specifications of your diversion or storage works.) Well to supply cold water for
State manner in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits.

	ated cost of works \$25,000.00	
IV. LAUM	ated time required to construct works3 years	
11 Fetim	ated time required to complete the application to beneficial use	
	rks: For use other than irrigation or stock watering, state number and type of units to be serve	
	mptive use.	
<u>It</u>	is proposed that up to 60 greenhouses will be constructed	ed. Wate
_wi]	ll be required on a 24 hour basis. 7 days per week for o	ooling
are	d watering. Estimated water requirements for each green 20 gallons per minute. Use map filed under Application port this application.	26626 t
Applicant	Agri-Technology Corporation	
Compared	By s/ Gena Kies Sec. Tres. 2209 Michael Dr. bs/sk dc/ga Carson City, Nev. 89701	
Compared.		
	APPROVAL OF STATE ENGINEER	
This i	s to certify that I have examined the foregoing application, and do hereby grant the same, su	bject to the
following li	mitations and conditions:	
ч	This permit is issued subject to existing rights. It is	
unders	stood that the amount of water herein granted is only a	
	<pre>cary allowance and that the final water right obtained this permit will be dependent upon the amount of water</pre>	••••
	ly placed to beneficial use. It is also understood that	
this r	right must allow for a reasonable lowering of the static	
	level. This well shall be equipped with a two (2) incheasuring depth to water. If the well is flowing, a valve	
TOT WE	asurring depth to water. It the west is frowing, a varve	
must b		
meter	e installed and maintained to prevent waste. A totalizi must be installed and maintained in the discharge pipeli	ng ne
meter near t	pe installed and maintained to prevent waste. A totalizi must be installed and maintained in the discharge pipeli he point of diversion and accurate measurements must be	ng ne
meter near t kept c	be installed and maintained to prevent waste. A totalizi must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter	ng ne must
meter near t kept o be ins	pe installed and maintained to prevent waste. A totalizi must be installed and maintained in the discharge pipeli he point of diversion and accurate measurements must be	ng ne must of
meter near t kept of be ins of Com an are	ne installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within the designated by the State Engineer, pursuant to NRS 534.	ng ne must of
meter near t kept o be ins of Com an are	be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Properties of Work is filed. This source is located withing a designated by the State Engineer, pursuant to NRS 534.	ngmust of
meter near t kept o be ins of Com an are	ne installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within the designated by the State Engineer, pursuant to NRS 534.	ngmust of
meter near t kept o be ins of Com an are	be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Properties of Work is filed. This source is located withing a designated by the State Engineer, pursuant to NRS 534.	ngmust of
meter near t kept of be ins of Com an are The St grante	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The retains the right to regulate the use of the water had at any and all times.	ngmust of
meter near t kept of be ins of Com an are The St grante	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The retains the right to regulate the use of the water had at any and all times.	ng
meter near t kept of be ins of Com an are The St grante	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The retains the right to regulate the use of the water had at any and all times.	ngne must of
meter near t kept of be ins of Com an are The St grante	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The retains the right to regulate the use of the water had at any and all times.	ng ne must of 030 erein
meter near t kept of be ins of Com an are The St grante	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The attentions the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7	ng ne must of 030erein ial use, and
meter near t kept of be ins of Com an are The St grante The amount not to exce 10.51 Actual cons	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prompletion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The retains the right to regulate the use of the water had at any and all times. The tof water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7	ng
meter near to kept of be ins of Com an are The St grante The amount not to excee 10.51 Actual cons Proof of co	must be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Propertion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534, ate retains the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second, but not to exceed the million gallons annually. Struction work shall begin on or before. February 17,	ng ne must of
meter near t kept of be ins of Com an are The St grante The amount not to exce 10.51 Actual cons Proof of co Work must	must be installed and maintained to prevent waste. A totalizi must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Properties of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The data any and all times. In the data any and all times are cubic feet per second, but not to exceed the water begins and to work shall be filed before. March 17, 19 The be prosecuted with reasonable diligence and be completed on or before. March 17, 19 March 17, 19 March 17, 19	ng
meter near t kept of be ins of Com an are The St grante The amoun not to exce 10.51 Actual cons Proof of co Work must Proof of co Application	nust be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be off water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Propertion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The attentions the right to regulate the use of the water had at any and all times. In the first of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second, but not to exceed million gallons annually. Struction work shall begin on or before. February 17, memonement of work shall be filed before. March 17, 19 be prosecuted with reasonable diligence and be completed on or before. February 17, mempletion of work shall be filed before. March 17, 19 and of water to beneficial use shall be made on or before. February 17, and the filed before is a february 18, and the filed before is a february 18, and	ng
meter near t kept of be ins of Com an are The St grante The amoun not to exce 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the	nee installed and maintained to prevent waste. A totalizimust be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be off water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Propertion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS.534. The retains the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second, but not to exceed million gallons annually. Struction work shall begin on or before. February 17, memencement of work shall be filed before. March 17, 19 the prosecuted with reasonable diligence and be completed on or before. February 17, mempletion of work shall be filed before. March 17, 19 the of water to beneficial use shall be filed on or before. February 17, and the filed before to beneficial use shall be filed on or before. March 17, 19 the application of water to beneficial use shall be filed on or before. March 17, 19 the application of water to beneficial use shall be filed on or before. March 17, 19 the application of water to beneficial use shall be filed on or before. March 17, 19 the application of water to beneficial use shall be filed on or before. March 17, 19 the application of water to beneficial use shall be filed on or before. March 17, 19 the application of water to beneficial use shall be filed on or before.	ng
meter near to kept of be ins of Com an are The St grante The amount not to exce 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the Map in sup	nee installed and maintained to prevent waste. A totalizimust be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be installed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Propertion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS.534. The retainst he right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second, but not to exceed million gallons annually. Struction work shall begin on or before. February 17, ammencement of work shall be filed before. March 17, 19 to water to beneficial use shall be filed on or before. February 17, appoint of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before.	ng
meter near to kept of be ins of Com an are The St grante The amount not to excee 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the Map in sup	nee installed and maintained to prevent waste. A totalizimust be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Properties of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS.534. The retains the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second. But not to exceed million gallons annually. Struction work shall begin on or before. February 17, ammencement of work shall be filed before. March 17, 19 to feet per second with reasonable diligence and be completed on or before. February 17, ampletion of work shall be filed before. March 17, 19 to few to beneficial use shall be filed on or before. February 17, appletion of water to beneficial use shall be filed on or before. March 17, 19 to for or for of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before.	ng must of
meter near to kept of be ins of Com an are The St grante The amount not to excee 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the Map in sup Commencem Completion of	nust be installed and maintained to prevent waste. A totalizing must be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be off water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Prophetion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS. 534. The data any and all times are retains the right to regulate the use of the water had at any and all times. The data any and all times are retained to be applied to beneficed. The data any and all times are retained to the amount which can be applied to beneficed. The data any and all times are retained to the amount which can be applied to beneficed. The data any and all times are retained to the amount which can be applied to benefice and at any and all times. The data any and all times are retained to the amount which can be applied to beneficed. The data any and all times are retained to the amount which can be applied to benefice and at any and all times. The data any and all times are retained to the amount which can be applied to benefice and at any and all times. The data any and all times are retained to be applied to beneficial use shall be filed on or before. The data and the discharge place and be completed on or before. The data and the discharge place are to beneficial use shall be filed on or before. The data and the discharge place and any and all times are retained to work filed FEB 2 2 1979. The data and accurate measurements and accurate measurements and accurate begins a	ng must of
meter near t kept of be ins of Com an are The St grante The amoun not to exce 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the Map in sup Commencem Completion of Proof of ben	nee installed and maintained to prevent waste. A totalizimust be installed and maintained in the discharge pipeliche point of diversion and accurate measurements must be of water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Properties of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS.534. The retains the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second. But not to exceed million gallons annually. Struction work shall begin on or before. February 17, ammencement of work shall be filed before. March 17, 19 to feet per second with reasonable diligence and be completed on or before. February 17, ampletion of work shall be filed before. March 17, 19 to few to beneficial use shall be filed on or before. February 17, appletion of water to beneficial use shall be filed on or before. March 17, 19 to for or for of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before. March 17, 19 to poor of proof of beneficial use shall be filed on or before.	ng must of
meter near t kept of be ins of Com an are The St grante The amoun not to exce 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the Map in sup Commencem Completion of Proof of bency Cultural man Certificate N	nustalled and maintained to prevent waste. A totalizimust be installed and maintained in the discharge pipelithe point of diversion and accurate measurements must be off water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Propertion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The cate retains the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed. 2.7 cubic feet per second. But not to exceed to water to be appropriated shall be filed before. February 17, mmencement of work shall be filed before. February 17, properties of water to beneficial use shall be filed on or before. February 17, properties of water to beneficial use shall be filed on or before. February 17, properties of water to beneficial use shall be filed on or before. February 17, properties of water to beneficial use shall be filed on or before. February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to beneficial use shall be filed on or before. March 17, 19 February 17, properties of water to be march 17, 19 February 17, properties of water to be march 17, 19 February 17, properties of wat	ng must of
meter near t kept of be ins of Com an are The St grante The amoun not to exce 10.51 Actual cons Proof of co Work must Proof of co Application Proof of the Map in sup Commencem Completion of Proof of bency Cultural map Certificate N	must be installed and maintained to prevent waste. A totalizimust be installed and maintained in the discharge pipelithe point of diversion and accurate measurements must be off water placed to beneficial use. The totalizing meter stalled before any use of water begins, or before the Propertion of Work is filed. This source is located within a designated by the State Engineer, pursuant to NRS 534. The water retains the right to regulate the use of the water had at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to beneficed at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to benefice at any and all times. It of water to be appropriated shall be limited to the amount which can be applied to benefice at any and all times. It of water to be appropriated shall be filed before. It is not a total in a	ng must of